













SPC-0830 MIMCIKI

## **Replacing Wiper Absorber**





This printer uses ultraviolet curable ink (UV ink).

When replacing the wiper absorber, be sure to wear the supplied goggles and gloves.

When "!REPLACE WIPER/ABSORBER" appears on the screen, check the wiper absorber.


If there is ink on the absorber as illustrated by the image to the right, replace the absorber.

The following items are packed in this kit.

Check them for correct quantities and appearance.

If you find any problems, please contact your distributor or a MIMAKI office.


| Wiper absorber4 units                                                |  |
|----------------------------------------------------------------------|--|
| Wiper absorber case4 units                                           |  |
| Instruction manual for the wiper absorber kit (this document) 1 copy |  |



In the local mode, press FUNC1 (MENU) first, press Tunct, and then select [MAINTENANCE] - [STATION] - [Replace WIPER].


"Replace WIPER" will be selected and the carriage will move to the left edge.

**9** Open the right maintenance cover.




Remove the wiper absorber.

To remove the absorber, push the hook down and pull out the absorber.



4 Install the new wiper absorber.



**5** Close the maintenance cover, and press the ENTER key. The warning will be reset.

6 Press the END/POWER key several times.

The machine returns to LOCAL.















Mail: encraje@encraje.fr | Tél. 02 47 43 09 17