



LARGE FORMAT  
PHOTO

# TRISOLV PHOTOART PAPER 210

glossy 3699, 210 g/m<sup>2</sup>

Premium, glossy photo paper for photorealistic prints for indoor and outdoor use

TriSolv PhotoArt is the right choice for the production of photo, art and advertising prints for indoor and outdoor applications with solvent, latex and UV inks. This multi-coated, weatherproof and water-resistant paper with a glossy surface finish impresses with a look and feel similar to photos and is characterised by very high colour brilliance and image definition. The material dries quickly even when printed with extremely large ink densities. This water-repellent product can be stuck to a wide range of smooth substrates such as wood or metal with wallpaper paste or double-side adhesive tape as easily as papering a wall. Prints are long-lasting and offer high scratch resistance and durability even without additional lamination.

## Technologies



## Properties



- Außenbeständig

## Advantages

- Excellent colour brilliance
- Photorealistic reproductions
- Homogeneous gloss in printed and unprinted areas
- Water-repellent surface
- High stiffness
- High scratch resistance



The mark of  
responsible forestry

## General tips

Please note when printing with any of the 300 and 500 series HP Latex printer, to print roll to roll!

The ink amounts must be adjusted for the paper. Please reduce the single colours cyan, magenta, yellow and black (ink restrictions) and lower the ink limit. This will not only help keep costs down but will also improve your drying performance.

Please follow the recommendations the printer and ink manufacturer provide. To achieve desired results please check the preheating and drying temperatures of the media before printing.

## Physical data

| Name                       | Value                     | Norm          |
|----------------------------|---------------------------|---------------|
| Weight [g/m <sup>2</sup> ] | 210                       | ISO 536       |
| Thickness (paper) [µm]     | 230                       | ISO 534       |
| Chromaticity (D50/2°) M0   | L* 94.3 a* 1.1 b*<br>-4.0 | ISO 13655, M0 |
| Gloss (85°)                | 78                        | ISO 2813      |
| Opacity [%]                | > 98                      | ISO 2471      |