

1. Identification

Product Name	: UV ink LF-200 Cyan
Order No.	: SPC-0591C
General Use	: Ink for ink jet printer
Product Description	: UV Inkjet Ink
SDS Number	: 037-U050561
Manufacture	
Company Name	: Mimaki Engineering Co., Ltd.
Address	2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN
Telephone No.	:+81-268-64-2413
Importer / Distributor Esta	ablished in USA
Company Name	: MIMAKI USA, INC.
Address	: 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.
Telephone No.	:+1-678-730-0170
Emergency Telephone No.	:+81-268-64-2281

2. Hazards Identification

[GHS Classification]	
Physical Hazards	
Flammable Liquids	: Not classified
Health Hazards	
Skin Corrosion / Irritation	Category 2
Eye Damage / Irritation	: Category 2A
Sensitization – Skin	Category 1
Toxic to Reproduction	: Category 2
Specific Target Organ Toxicity	: Category 2 (skin)
(Repeated Exposure)	

The above list does not include category being non-classifiable or not-applicable.

[GHS Label Elements] Symbol





Signal Word Warning Hazard Statements H315 Causes skin irritation H317 May cause an allergic skin reaction H319 Causes serious eve irritation H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged or repeated exposure (Skin) **Precautionary Statements** [Prevention] P201 Obtain SDS (Safety Data Sheet) and printer's operation manual before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe gas/mist. P264 Wash hands thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection. [Response] P302+P352 IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. P314 Get medical advice/attention if you feel unwell. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash before re-use. [Storage] P405 Store locked up. [Disposal] P501 Dispose of contents/container in accordance with local/regional/national/international regulation (to be specified).

NFPA Rating (scale 0 - 4)

Health = 2 Flammability = 1 Instability = 2 Special = None



3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.
1	ISOBORNYL ACRYLATE	45 - 60	5888-33-5
2	AMINE MODIFIED ACRYLATE OLIGOMER	10 - 20	Trade Secret
3	DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	5 - 15	7328-17-8
4	2,4,6-Trimethylbenzoyldiphenylphosphine oxide	5 - 15	75980-60-8
5	TETRAHYDROFURFURYL ACRYLATE	5 - 15	2399-48-6
6	SUBSTITUTED TRIAZINE	0 - 10	Trade Secret
7	1,6-HEXANEDIOL DIACRYLATE	1 - 10	13048-33-4
8	9H-Thioxanthen-9-one, 2,4-diethyl-	1 - 10	82799-44-8
9	C.I. PIGMENT BLUE 15	1 - 10	147-14-8

4. First Aid Measures

Inhalation	Remove person to fresh air. If you feel unwell, get medical attention.
Eye Contact	: Immediately flush with large amounts of water. Remove contact
	lenses if easy to do. Continue rinsing. Get medical attention.
Skin Contact	: Immediately wash with soap and water. Remove contaminated
	clothing and wash before reuse. If signs/symptoms develop,get
	medical attention.
Ingestion	Rinse mouth. If you feel unwell, get medical attention.
Most important	: See Section 11.1. Information on toxicological effects.
symptoms and effects,	
both acute and delayed	
Indication of Immediate	: Not applicable.
Medical Attention and	
Special Treatment	
Needed, If Needed	



5. Fire Fighting Measures

Flammable Properties	: Flash point $>200^{\circ}$ F
Extinguishing Media	: Use a fire fighting agent suitable for ordinary combustible material
	such as water or foam to extinguish.
Special Hazards Arising	: Closed containers exposed to heat from fire may build pressure and
from the Chemical	explode.
Hazardous Combustion	Carbon monoxide, Carbon dioxide (During Combustion)
Products	
Special protective actions	: Water may not effectively extinguish fire; however, it should be used
for fire-fighters	to keep fire-exposed containers and surfaces cool and prevent
	explosive rupture.

6. Accidental Release Measures

Personal precautions,	: Evacuate area. Ventilate the area with fresh air. For large spill, or
protective equipment and	spills in confined spaces, provide mechanical ventilation to disperse
emergency procedures	or exhaust vapors, in accordance with good industrial hygiene
	practice. Warning! A motor could be an ignition source and could
	cause flammable gases or vapors in the spill area to burn or explode.
	Refer to other sections of this SDS for information regarding
	physical and health hazards, respiratory protection, ventilation, and
	personal protective equipment.
Environmental	Avoid release to the environment. For larger spills, cover drains and
precautions	build dikes to prevent entry into sewer systems or bodies of water
Methods and material for	: Contain spill. Working from around the edges of the spill inward,
containment and cleaning	cover with bentonite, vermiculite, or commercially available
up	inorganic absorbent material. Mix in sufficient absorbent until it
	appears dry. Remember, adding an absorbent material does not
	remove a physical, health, or environmental hazard. Collect as much
	of the spilled material as possible. Place in a closed container
	approved for transportation by appropriate authorities. Clean up
	residue with an appropriate solvent selected by a qualified and
	authorized person. Ventilate the area with fresh air. Read and follow
	safety precautions on the solvent label and SDS. Seal the container.

MIMCIKI Safety Data Sheets

Dispose of collected material as soon as possible.

7.	Handliı	ng and	Storage
----	---------	--------	---------

Precautions for Safe	Avoid skin contact with hot material. For industrial or professional
Handling	use only. Do not handle until all safety precautions have been read
	and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do
	not get in eyes, on skin, or on clothing. Do not eat, drink or smoke
	when using this product. Wash thoroughly after handling.
	Contaminated work clothing should not be allowed out of the
	workplace. Avoid release to the environment. Wash contaminated
	clothing before reuse. Avoid contact with oxidizing agents (eg.
	chlorine, chromic acid etc.) Use personal protective equipment
	(gloves, respirators, etc.) as required.
Conditions for Safe	: Protect from sunlight. Store away from heat. Store away from
Storage, including any	oxidizing agents.
Incompatibilities	

8. Exposure Controls / Personal Protection

Exposure Limit Values : If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS No.	Agency	Limit type	Additional
				Comments
1,6-HEXANEDIOL	13048-33-4	AIHA	TWA:1 mg/m ³	Dermal
DIACRYLATE			(0.11 ppm)	Sensitizer
TETRAHYDROFURFURYL	2399-48-6	Manufacturer	TWA:0.1 ppm	
ACRYLATE		determined	$(0.64 \text{mg/m}^3);$	
			STEL:0.3 ppm(1.91	
			mg/m ³)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

MINCIKI Safety Data Sheets

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit CEIL: Ceiling

Exposure Controls

Occupational Exposure Controls

Appropriate Engineering Controls : Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

Personal Protection

Respiratory Protection



Skin/Hand Protection



: An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure: Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates For questions about suitability for a specific application, consult with your respirator manufacturer.

: Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

MIMCIKI[®] Safety Data Sheets

 Eye Protection
 : Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Indirect Vented Goggles

9. Physical and Chemical Properties

Glasses

Appearance	- Physical State	: Liquid	
	- Color	: Cyan	
Odor		: Acrylate Odor,	
pН		: Not available	
Boiling Point	/ Boiling Range	$:>200^{\circ}$ F	
Melting Point	/ Melting Range	: Not available	
Decomposition	n Temperature	: Not available	
Flash Point		$:>200^{\circ}$ F	
Auto ignition	temperature	: Not available	
Flammability	(Solid, Gas)	: Not Applicable	
Explosive Pro	perties	: Not available	
Oxidizing Pro	perties	: Not available	
Upper / Lower Flammability or		: Not available	
Explosive Limits			
Vapor Pressu	re	: < 10 mmHg [@ 20 °C]	
Specific Gravi	ity	: 1.04 [Ref Std: WATER=1]	
Solubility		: Not available	
Water Solubil	ity	: Negligible	
Partition Coefficient (n-octanol / Water)		: Not available	
Viscosity		: Not available	
Vapor Density		:>1 [Ref Std: AIR=1]	
Evaporation I	Rate	: Not available	
VOC		: Not available	



10. Stability and Reactivity

Reactivity	[:] This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.
Chemical Stability	: Stable under normal conditions of use.
Possibility of Hazardous	: Hazardous polymerization may occur. (Upon depletion of inhibitor or
Reactions	exposure to heat)
Conditions to Avoid	: Heat
Incompatible Materials	: Strong oxidizing agents
Hazardous	: None known.
Decomposition	

Refer to section 5.2 for hazardous decomposition products during combustion

11. Toxicological Information	
Inhalation	: Respiratory Tract Irritation: Signs/symptoms may include cough,
	sneezing, nasal discharge, headache, hoarseness, and nose and throat
	pain.
Skin Contact	: Skin Irritation: Signs/symptoms may include localized redness,
	swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin
	Reaction (non-photo induced) in sensitive people: Signs/symptoms
	may include redness, swelling, blistering, and itching.
Eye Contact	: Severe Eye Irritation: Signs/symptoms may include significant
	redness, swelling, pain, tearing, cloudy appearance of the cornea, and
	impaired vision
Ingestion	: May be harmful if swallowed. Gastrointestinal Irritation:
	Signs/symptoms may include abdominal pain, stomach upset, nausea,
	vomiting and diarrhea.
Additional Health Effect	s:
Prolonged or repeated	: Dermal Effects: Signs/symptoms may include redness, itching, acne,
exposure may cause	or bumps on the skin.
target organ effects:	



Reproductive/Developme	: Contains a chemical or chemicals which can cause birth defects or
ntal Toxicity:	other reproductive harm.

12. Ecological Information

	Handling is noted because it might influence the environment when leaking and abandoning it. Especially, note that the product doesn't flow directly to ground, the
	river, and the drain ditch.
Ecotoxicity	: Please contact the address or phone number listed on the first page of
	the SDS for additional chemical fate information on this material
	and/or its components.
Persistence and	: Not available
Degradability	
Bioaccumulation	: Not available
Mobility	: Not available
Other Toxicity	: Not available

13. Disposal Considerations

: Comply with all USA, national and local regulations. Do not release to water. Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Do not dump this product into sewers, on the ground or into any body of water.



EPA Hazardous Waste : Not regulated Number (RCRA)

14. Transport Information

	Check a thing without a leak in a container.
	Perform prevention of collapse of cargo surely.
UN Number	: UN3082
Shipping	: Environmentally hazardous substance, liquid, n.o.s.
Name	(Contains: ISOBORNYL ACRYLATE,
	1,6-HEXANEDIOL DIACRYLATE)
Hazardous Class or	: 9
Division	
Packing Group (PG)	: III
Marine Pollutant	: Yes
Remarks	: Single or inner packaging less than 5 L (liquid) or 5 kg net (solids) is
	excepted from Dangerous Goods regulations.
	Refer to ICAO/IATAA197, IMDG 2.10.2.7, ADR SP 375.

15. Regulatory Information

U.S. Federal Regulations

: Immediate Hazard: Yes		
Delayed Hazard: Yes		
Fire: No		
Pressure: No		
Reactive: No		
:		
Ingredient	CAS No.	%
DIETHYLENE GLYCOL ETHYL ETHER	7999 17 9	F 1 F
ACRYLATE (GLYCOL ETHERS)	1920-11-8	5 - 15
	Fire: No Pressure: No Reactive: No : Ingredient DIETHYLENE GLYCOL ETHYL ETHER	Delayed Hazard: Yes Fire: No Pressure: No Reactive: No : Ingredient CAS No. DIETHYLENE GLYCOL ETHYL ETHER 7328-17-8



This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient	CAS No.	Regulation	Status
9H-Thioxanthen-9-one, 2,4-diethyl-	82799-44-8	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Applicable

This material contains a chemical regulated by an EPA Significant New Use Rule (TSCA Section 5)

Ingredient	CAS No.	Reference
9H-Thioxanthen-9-one, 2,4-diethyl-	82799-44-8	40CFR721.9664

California Proposition	: WARNING
65	This product can expose you to chemicals including Toluene,
	which is known to the State of California to cause birth defects or
	other reproductive harm. For more information go to
	www.P65Warnings.ca.gov.
Chemical Inventories	: The components of this product are in compliance with the chemical
	notification requirements of TSCA.

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.